



Item No.	KTP-002
Material	ABS, PS, PP
Length	39 cm
Width	
Weight	
Color	
MOQ	3000pcs
Lead time	7-10 days
Payment	T/T & L/C
Shipping	By sea, air, or express
Notes	1. 1pc PE bag per 1pc 2. 10pcs per box 3. K = K 4. ...
Quantity	150000-300000
Lead time	30-35 days
Payment	T/T, L/C, ...
Shipping	By sea, air, or express
Notes	1. ... 2. ... 3. ... 4. ... 5. ...





□□ □□□□



□□□ □□ □□□□ □□ □□ □□□ □□ □ □□, □□ □□□□ □□□□□□ □□ □□.

□□□□ □ □ □□:

□□ □□, □□ □□, □□ □□ □□ □□ □□ □□ □ □ □, □□ □ □□ □□, □□ □□, □□□□ □□ □□, □ □□ □□ □ □ □□ □ □□.

□□□□ □ □ □□:

nickeling (nickel plating) is a process of electroplating a thin layer of nickel onto a metal surface. It is commonly used for corrosion protection and decorative purposes. The process involves immersing the metal part in a nickel sulfate solution and passing an electric current through it.

nickeling



nickeling is a process of electroplating a thin layer of nickel onto a metal surface. It is commonly used for corrosion protection and decorative purposes. The process involves immersing the metal part in a nickel sulfate solution and passing an electric current through it.

nickeling is a process of electroplating a thin layer of nickel onto a metal surface. It is commonly used for corrosion protection and decorative purposes. The process involves immersing the metal part in a nickel sulfate solution and passing an electric current through it.

nickeling is a process of electroplating a thin layer of nickel onto a metal surface. It is commonly used for corrosion protection and decorative purposes. The process involves immersing the metal part in a nickel sulfate solution and passing an electric current through it.

nickeling is a process of electroplating a thin layer of nickel onto a metal surface. It is commonly used for corrosion protection and decorative purposes. The process involves immersing the metal part in a nickel sulfate solution and passing an electric current through it.

nickeling is a process of electroplating a thin layer of nickel onto a metal surface. It is commonly used for corrosion protection and decorative purposes. The process involves immersing the metal part in a nickel sulfate solution and passing an electric current through it. debossed, is a process of creating a recessed design on a surface.

knids



knids is a process of creating a recessed design on a surface. It is commonly used for decorative purposes and to create a textured surface. The process involves using a die to press a design into a material.

knids

... world.the ... environmental.we ... commodity.what

... world.the ...

... environmental.we ... 80%

... commodity.what

... ?

... "..."